




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>5</sup> :  G09G 3/02	A1	(11) International Publication Number: WO 94/03887  (43) International Publication Date: 17 February 1994 (17.02.94)
<p>(21) International Application Number: PCT/US93/07233</p> <p>(22) International Filing Date: 2 August 1993 (02.08.93)</p> <p>(30) Priority data: 07/924,623 4 August 1992 (04.08.92) US</p> <p>(71)(72) Applicants and Inventors: McCLISH, Richard, E., D. [US/US]; 1739 Addison, #15, Berkeley, CA 94703 (US). GUNN, Gary, J. [US/US]; 549. Santa Barbara Rd., Berkeley, CA 94707 (US). KLEIR, Richard, L. [US/US]; 2634 Claremont, Berkeley, CA 95705 (US).</p> <p>(74) Agent: GRUNEWALD, Glen, R.; 166 Santa Clara Avenue, Oakland, CA 94610 (US).</p>		<p>(81) Designated States: JP, KR, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p><b>Published</b> With international search report. With amended claims.</p>

## (54) Title: IDEOGRAPHIC CHARACTER SELECTION METHOD AND APPARATUS



## (57) Abstract

An interactive keyboard and display apparatus (1) is used to enter ideographic characters in a computer or other utilisation device. The characters are defined by manually selecting displayed symbols such as phonemes (23, 23A), strokes (21, 21A), radicals (22) and inflective tones (26, 26A) represented in displayed key cells which are arranged in a matrix for rapid selection. Simultaneous multiple key cell selection is possible for accelerated character entry. The keyboard and display (1) are integrated in a format suitable for replacing conventional keyboards. To avoid spurious entries, a pre-determined amount of pressure must be applied to the display panel (12) when entering a symbol or character.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NE	Niger
BE	Belgium	GN	Guinea	NL	Netherlands
BF	Burkina Faso	GR	Greece	NO	Norway
BG	Bulgaria	HU	Hungary	NZ	New Zealand
BJ	Benin	IE	Ireland	PL	Poland
BR	Brazil	IT	Italy	PT	Portugal
BY	Belarus	JP	Japan	RO	Romania
CA	Canada	KP	Democratic People's Republic of Korea	RU	Russian Federation
CF	Central African Republic	KR	Republic of Korea	SD	Sudan
CG	Congo	KZ	Kazakhstan	SE	Sweden
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovak Republic
CM	Cameroon	LU	Luxembourg	SN	Senegal
CN	China	LV	Latvia	TD	Chad
CS	Czechoslovakia	MC	Monaco	TG	Togo
CZ	Czech Republic	MG	Madagascar	UA	Ukraine
DE	Germany	ML	Mali	US	United States of America
DK	Denmark	MN	Mongolia	UZ	Uzbekistan
ES	Spain			VN	Viet Nam
FI	Finland				

## **IDEOGRAPHIC CHARACTER SELECTION METHOD AND APPARATUS**

### **TECHNICAL FIELD**

The present invention relates to text entry systems and more specifically to a multiple-image interactive system for selecting ideographic characters and symbols.

### **BACKGROUND ART**

It is known that alphanumeric keyboards are quite inappropriate for writing ideographic character-based written languages such as Chinese and Japanese. These ideographic languages typically use thousands of characters, each of which would typically require a separate key, thus making the resulting keyboard unduly large and extremely taxing on the user's vision and memory.

As a result, current phonetic entry systems such as Bopomofo and Pinyin have been developed whereby a desired ideographic character is displayed upon keyboard entry of phonetic elements corresponding to its pronunciation. Unfortunately in such systems, phonetic construction alone rarely produces a single ideographic character. In Chinese, for example, homonyms are very common. Such systems often require the user to select a desired character from a displayed group, following the complete entry of the corresponding phonetic symbols : a slow and laborious process.

Pen-based character entry systems allow the user to define a desired character by entering a series of 'brush' strokes. Since a complex character may not be defined until the 7th or 8th stroke, this system is also quite slow and tedious.

### **OBJECTS OF THE INVENTION**

It is therefore a general object of the present invention to provide an interactive system for manually selecting ideographic characters of written language.

It is a more specific object of the present invention to provide an integrated keyboard and display apparatus for performing rapid ideographic character entry without need for extensive training.

### **SUMMARY OF THE INVENTION**

According to the invention, an interactive apparatus allowing a user to enter ideographic characters of written language into a utilisation device, such as a computer, comprises an integrated keyboard/display unit which displays a matrix of manually selectable key cells among which a user can select character-construction elements, phonetic and conceptual symbols related to a desired ideographic character to be entered. The apparatus may also display key cells pertaining to numbers and punctuation, for direct manual selection of the displayed symbol.

In the character selection process, a user selects remembered elements pertaining to a desired character to be entered. The selection of each of these remembered elements, such as phonemes, primary stroke, primary radical, etc., progressively restricts the number of eligible characters down to a single possible character. Upon final selection by the user, a character command corresponding to the single possible character is emitted by a data processor responsive to previous key cell selections.

In a preferred embodiment, the data processor displays a small cluster of possible ideographic characters for direct manual selection thereof, once the number of possible characters has been sufficiently reduced by previous symbol selection. More than one character displayed in this cluster may be selected directly for additional acceleration of the character selection process.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 is a cutaway view of an apparatus according to the present invention.

FIG.2 is a plan view of a visible image displayed by the LCD display panel of the apparatus of FIG.1.

FIG.3 shows a variation of the displayed image of FIG.2 featuring additional key cell functions.

FIG. 4 is a plan view of another image displayed by the LCD display panel, showing a different key cell arrangement of the same functional groups.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to FIG.1, an integrated keyboard/display unit 1 comprises a data processor 11, a liquid crystal display (LCD) panel 12 and a framed infrared (IR) sensor matrix 13.

The IR sensor matrix 13 is of a conventional type, responsive to the obstruction of light beams generated therein preferably in close proximity of the top surface of the LCD display panel 12 to avoid parallax errors. The IR sensor matrix 13 is used to determine the location of a finger pointing at a displayed item to be selected.

An enclosure 10 contains the data processor 11, supports the LCD display panel 12 through a resilient suspension 14, and supports the framed IR sensor matrix 13 in a substantially fixed lateral position with respect to the LCD display panel 12, so that a fixed correspondence exists between the location of image elements displayed by the LCD display panel 12 and the location of the framed sensor matrix 13.

When performing a manual selection of a displayed image element on the LCD display panel 12, the resilient suspension 14 allows the LCD display panel 12 to be depressed towards the inside of the enclosure 10 upon exerting a pressure on a portion of the displayed image.

A switch 15 mounted onto the data processor's 11 circuit board has an actuator 16 contacting the undersurface of the LCD display panel 12. The switch 15 changes state when the LCD display panel 12 is depressed by a sufficient amount, as a result of performing a manual selection of a displayed image element. The switch is electrically connected to the data processor's 11 circuitry, so that the data processor 11 can associate the depression of the LCD display panel 12 with the sensed coordinates of the interruption of a pair of light beams in the framed sensor matrix 13, thus becoming responsive to a manual selection of a displayed image element.

It has been found preferable to have a detent mechanism for providing a tactile indication of manual selection of a displayed image element. This detent mechanism is incorporated in the switch 15 in the present embodiment, although it can be incorporated in the elastomeric suspension 14 or otherwise provided using known means for a similar purpose.

---

For ease of explanation of the present invention, the preferred embodiment will be described for use with the Chinese language, although this is not to be construed as a limitation of the present invention.

Referring now to FIG.2, pertaining to a first embodiment of the present invention, the LCD panel 12 displays an image composed of matrixed key cells which are grouped in a manner to optimize the speed of recognition and selection of a desired ideographic character among the many thousands currently in usage. Each key cell represents a manually selectable symbol. In the present description, the manual selection of a symbol or character means the manual selection of a key cell representing this symbol or character.

The key cells are categorized and grouped as follows:

Strokes 21 & 21A symmetrically disposed in opposite vertical columns for rapid two-hand selection; Radicals 22 disposed in a 14 X 17 cell matrix between the Strokes 21 and 21A; Bopomofo/Pini-Yin key cells 23 underlying the Radicals 22 and the Strokes 21 and 21A; a Symbol Set Selection key 24 for selecting either Bopomofo or Pin-Yin symbols to be displayed in the Bopomofo/Pini-Yin key cells 23; Punctuation and Foreign Character key cells 25; Inflective Tones 26 used to select inflections of phonetic utterances corresponding to selected Bopomofo/Pini-Yin key cells 23 during the character selection process; Target Characters 27 which appear during the character selection process; Text Entry key cells 28 and 28A, symmetrically disposed at the lower corners of the image, for transmitting 'write instruction' signals as they are normally used in the art; a Clear key 29 for erasing a symbol selection sequence; a Spacebar key 30 for entering a space between characters, as it is normally used in the art; a Backspace key 31 for deleting a character in text, as it is normally used in the art; a Last Entry window 32, displaying the last item entered in text; a Semantic Definition window 33, displaying the semantic definition of the item displayed in the Last Entry window 32, when applicable; and a Log window 34 for displaying selected symbols in the order of selection during the character selection sequence.

In FIG. 2, the Log window 34 shows a character selection sequence wherein a radical 22 was first selected, followed by a stroke 21 or 21A, and a Bopomofo phoneme symbol 23. Referring now to FIG.3, the Log window 34 displays a similar character selection sequence wherein Pin-Yyin symbols were selected after the manual selection of a stroke 21 or 21A. An Inflective Tone 26 was then selected which defined a single Target Character 27 which may be entered in text by selecting it directly or by selecting a Text Entry key cell 28.

A user selects an ideographic character of written language by manually selecting symbols pertaining to the character. As the symbols are manually selected, the data processor 11 progressively excludes unrelated ideographic characters from a mass of stored ideographic characters typically contained in a memory file, until enough manual selections have been made to define a very limited group of Target Characters 27 for final manual selection of the desired character therein.

It is also possible to continue to manually select symbols until a single character has been defined, irrespectively of displayed Target Characters 27, in order to allow the greatest convenience of use of the present invention.

It is not necessary to select from all categories of symbols to define the desired character. This is helpful because the user can use whatever is remembered about a character and enter the available information to rapidly define the character. For example, a user may select a primary radical 22 of written language and also a first phoneme 23 of spoken language, the cumulative effect of which will typically limit the number of possibly related characters to a small group of Target Characters 27 displayed for direct selection of the desired character.

Referring now to FIG.4, an alternate disposition of the matrixed key cells is shown wherein the target characters 27, the strokes 21 & 21A and the inflective tones 26 & 26A are grouped in the center of the keyboard immediately above a central bottom row of key cells formed by the Enter keys 28 & 28A, the Clear key 29, the Spacebar key 30, the Backspace key 31 and the Pin-Yin/Bopomofo key 24. The phonemes 23 & 23A are grouped on each side of the strokes 21 & 21A and Inflective Tones 26 & 26A. The punctuation and Foreign character keys 25 & 25A occupy the lower corners of the image. The radicals 22 & 22A occupy the upper corners of the image and are disposed around a central top row of key cells formed by the Semantic Definition window 33, the Last Entry window 32 and the Log window 34.

This cluster approach to key cell grouping accelerates the selection process for users who select radicals less often than other symbols in order to define a character.

Many variations of the present invention will suggest themselves to persons of ordinary skill in the art. It is intended therefore that the foregoing description be considered as exemplary only and that the scope of the invention be ascertained by the following claims.

**WHAT IS CLAIMED IS :**

1. An integrated keyboard and display apparatus for selecting ideographic characters of written language, said apparatus comprising:

display means for producing an image comprising:

a first group of adjacent and manually selectable key cells pertaining to phonetic symbols of spoken said language, for manual selection of a said symbol displayed therein,

a second group of adjacent and manually selectable key cells pertaining to symbols representative of primary construction elements of said ideographic characters of said written language, for manual selection of a said symbol displayed therein,

a third group of adjacent and manually selectable key cells pertaining to symbols related to a meaning of each of said ideographic characters of said written language, for manual selection of a said symbol displayed therein,

sensing means responsive to a said manual selection of a said symbol,

data processing means cooperating with said display means and responsive to a plurality of said manual selections of said symbols displayed in said key cells, whereby said plurality of said manual selections of said symbols ultimately defines a desired said ideographic character, and

means for transmitting a signal indicative of said desired ideographic character to utilisation means.

2. The apparatus of claim 1 further comprising:

a fourth group of adjacent and manually selectable key cells pertaining to selectable said ideographic characters, for manual selection of a desired said ideographic character displayed therein.

3. The apparatus of claim 1 wherein said sensing means are responsive to an effectively simultaneous manual selection of a plurality of displayed elements of a said image, for reducing a time period required to find and select a desired ideographic character.

4. The apparatus of claim 1 wherein said data processing means further comprise means responsive to a signal indicative of an acknowledgement of reception by said utilisation means of said signal indicative of said desired ideographic character.



-7-

5. The apparatus of claim 1 wherein said sensing means include pressure-actuated means for activating said means for transmitting said signal indicative of said desired ideographic character upon application of a pre-determined amount of pressure on said display means.

## AMENDED CLAIMS

[received by the International Bureau on 13 January 1994 (13.01.94);  
original claims 1 and 5 amended; other claims unchanged (2 pages)]

1. An integrated keyboard and display apparatus for selecting ideographic characters of written language, said apparatus comprising:

display means for producing an image comprising:

a first group of manually selectable key cells each of which represents and displays a selectable phonetic symbol of spoken said language, for manual selection of said symbol displayed therein,

a second group of manually selectable key cells each of which represents and displays a selectable symbol representative of a primary construction element of each of said ideographic characters of said written language, for manual selection of said symbol displayed therein,

a third group of manually selectable key cells each of which represents and displays a selectable symbol representative of a conceptual element common to a plurality of said ideographic characters of said written language,

sensing means responsive to a selection of a said selectable symbol,

data processing means cooperating with said display means and responsive to a plurality of said manual selections of said selectable symbols displayed in said key cells, wherein ideographic characters unrelated to previously selected said selectable symbols are eliminated from a set of candidate ideographic characters upon each said selection of a selectable said key cell, whereby said plurality of said selections of said selectable symbols ultimately defines a desired said ideographic character, and

means for transmitting a signal indicative of said desired ideographic character to utilisation means.

2. The apparatus of claim 1 further comprising:


a fourth group of adjacent and manually selectable key cells pertaining to selectable said ideographic characters, for manual selection of a desired said ideographic character displayed therein.


3. The apparatus of claim 1 wherein said sensing means are responsive to an effectively simultaneous manual selection of a plurality of displayed elements of a said image, for reducing a time period required to find and select a desired ideographic character.

4. The apparatus of claim 1 wherein said data processing means further comprise means responsive to a signal indicative of an acknowledgement of reception by said utilisation means of said signal indicative of said desired ideographic character.


5. The apparatus of claim 1 wherein said sensing means are touch-sensitive, and wherein said means for transmitting said signal indicative of said desired ideographic character is actuated by further applying a pre-determined amount of pressure on a selected said key cell representative of said desired ideographic character.

1/4





3/4



27 FIG. 3




FIG. 4

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US93/07233

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(5) : G09G 3/02

US CL : 340/712

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : US: 340/706, 711, 712, 735, 751; 341/22, 23; 400/110, 109, 484

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US, A, 4,725,694 (Auer et al.), 16 February 1988, see Figs. 1-6.	1-5
Y	US, A, 4,954,955 (Chiu), 04 September 1990, see Fig. 3 and abstract.	1-5
Y	US, A, 5,131,766 (Wong), 21 July 1992, see Figs. 5F-5H.	1-5
A	US, A, 4,531,119 (Nakayama et al.) 23 July 1985, see abstract and Figs. 2- 4.	1-5

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A document defining the general state of the art which is not considered to be part of particular relevance	*X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*E earlier document published on or after the international filing date	*Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Z document member of the same patent family
*O document referring to an oral disclosure, use, exhibition or other means	
*P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

08 September 1993

Date of mailing of the international search report

17 NOV 1993

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231Authorized officer  
*Alvin Oberley*  
ALVIN OBERLEY

Facsimile No. NOT APPLICABLE

Telephone No. (703) 305-4721